



www.yoke.net

-- An ISO 9001 Certified Company --

YOKE INDUSTRIAL CORP.

#39, 33RD Road, Taichung Industrial Park
Taichung 407, Taiwan
Tel : 886-4-2350-8088
Fax : 886-4-2350-1001
E-Mail : yoke777@ms74.hinet.net



Retractable Lifeline – Wire Rope– DATA SHEET

Model: **Dash risk**

N-9450LECE-20/DZ

N-9450LECE-33/DZ

N-9450LECE-50/DZ

N-9450LECE-66/DZ

Standard: EN 363:2023

Type: Wire Rope SRL

Block-LECE

1. Product Description

The retractable lifeline N-9450LECE is a fall arrest block designed for situations that require fall protection in order to give personnel unhindered movement.

2. Main Features

Feature	Description
Fall Arrest Attachment Point	Rotating ring on top of the housing
Cable Material	Galvanized steel cable
Hook Material	N-2857, Aluminum, SAE7075
Weight	N-9450LECE-20/DZ : 4.0kg N-9450LECE-33/DZ : 4.7kg N-9450LECE-50/DZ : 7.1kg N-9450LECE-66/DZ : 9.4kg
Color	Red Housing
User Capacity	140 kg (including tools and clothing)





www.yoke.net

-- An ISO 9001 Certified Company --

YOKE INDUSTRIAL CORP.

#39, 33RD Road, Taichung Industrial Park
Taichung 407, Taiwan
Tel : 886-4-2350-8088
Fax : 886-4-2350-1001
E-Mail : yoke777@ms74.hinet.net



3. Compliance and Testing

- Conforms to EN 360:2023 – Personal fall equipment – Retractable type fall arresters.
- Max arrest distance: 1.4M
- Max arrest force: 6KN
- Inspection: 100% visual inspection, and 1 piece out of every 100 will undergo a drop test.

4. Applications

- Fall protection system (with connector and anchor conforming to EN)
- Construction, tower climbing, maintenance, and general work-at-height

5. Instructions for Use

- Ensure working area is free from hazards and obstructions that could interfere with the working of the device or cause harm to the user. Adjust the five adjustment points to ensure a snug fit before use.
- Inspect all equipment before each use as per the manufacturer's instructions.
- All equipment should be inspected on a regular basis by a competent qualified person.
- A competent person must ensure the systems compatibility will not allow accidental disengagement.

6. Packaging & Storage

- Supplied in individual carton box with instruction manual
- Store in a dry, clean area away from UV light and chemicals

7. Service Life & Inspection

- Expected service life: up to 3-5 years from manufacturing date (depending on conditions of use or storage space)
- Inspection:
 - Pre-use check by user before each use
 - Formal inspection by competent person every time before use.





www.yoke.net

-- An ISO 9001 Certified Company --

YOKE INDUSTRIAL CORP.

#39, 33RD Road, Taichung Industrial Park
Taichung 407, Taiwan
Tel : 886-4-2350-8088
Fax : 886-4-2350-1001
E-Mail : yoke777@ms74.hinet.net



Address : #39, 33rd Road, Taichung Industrial Park, Xitun
District, Taichung 407 Taiwan:

Tel: 886-4-2350-8088

Fax: 886-4-2350-1001

